

# PATRIA

## BAGGAGE TRACTORS PTD 25 TL-1



PTD 25 TL-1 Diesel Baggage Towing Tractors is a scientific ergonomics design that offer high reliability tractors and comfort.

PTD 25TL-1 is design for towing and pushing work in airport, post, warehouse, factory and so on. Optimized transmission system matches with engine power output perfectly. It is design by hydraulic powered transmission and high quality engine with latest environment requirement.

*EURO III Emission Standards Engine by  
ISUZU Technology*



- The Frame is of welded structure with high strength and the casted counterweight improves tractor stability and shock resistance
- Small tractors body length and wheel base improve stability
- Large fuel Tank ensures single shift consumption requirement
- Minimum under ground clearance is 150 mm meeting civil aviation



- Adjustable seat with save armrest and belt is assembled on the truck
- Driver can observe the tow hook directly from the seat



## PTD 25 TL-1 POWERFULL BAGGAGE TOWING TRACTORS

### TECHNICAL PARAMETER

Model	unit	PTD 25 TB
1. Max. Drawbar pull	kN	25
2. Max. Travel speed (unloaded)	km/h	18/15
3. Gradability (unloaded)	%	30
4. Min. Turning Radius	mm	<=3250
5. Brake Distance (20 km/h)	m	<-5
6. Weight	kg	3660
7. AXLE LOAD		
- Front Axle	kg	1000
- Rear Axle	kg	2660
8. ENGINE		
- Model		IsuzuTech JX493Z3G
- Cylinder bore x stroke	mm	4-95.4x107
- Rated Power	Kw/rpm	36/2450
- Max. Torque	Nm/rpm	170/1700
9. Fuel Tank Volume	L	65
10. DIMENSION		
- Length	mm	3050
- Width	mm	1390
- Height	mm	1370
11. Wheelbase	mm	1780
12. TREAD		
- Front Wheel	mm	1200
- Rear Wheel	mm	1180
13. Min. ground clearance	mm	150
14. Height between seat center line and ground	mm	450 (Option)
15. Voltage/capacity	V/Ah	12V/80
16. DRIVE AXLE		
- Model		P2L3-00011
- Toal Reduction ratio		7.647
17. TRANSMISSION BOX		
- Model		YYXZ25H
- Type		Stepless speed change torcon-YQB265
18. BRAKE		
- Service Brake		Hydraulic four wheel powered brake
- Parking Brake		Mechanical brake, rear wheel
19. TIRE		
- FR Size/Pressure	PR/kPa	6.50-10-10PR/790
- RR Size/Pressure	PR/kPa	7.00-15-12PR/860

### DRIVE AXLE





### FULL HYDRAULIC STEERING



### DASHBOARD & INSTRUMENTS



### FRAME



**Standard** : Double Seats, Rear view mirror, fire extinguisher, head light, full hydraulic power steering Instrument (speed, fuel, temp etc.), white painting, operator tool kits.

**Option** : cabin , customer color painting.



*Authorized Distributor*



**PT. Cyberindo Sinarbhakti**

Office & Factory:

Jalan Raya Kampung Melayu No. 38 RT/RW: 01/01

Teluk Naga Tangerang Indonesia 15510

Ph: +62-21-559138638 (Hunting) ; Fax: +62-21-55915725

Email : cyberonline@cbn.net.id